DELABIE

TEMPOMATIC tap with BIOCLIP spout

Ref. 20804T2

Electronic wall-mounted tap with stainless steel spout

2025 UK public price excluding VAT: £523.63

DESCRIPTION

TEMPOMATIC tap with BIOCLIP spout - Ref. 20804T2

Wall-mounted electronic basin tap for mounting on panels. Electronic tap with BIOCLIP removable spout Infrared tap supplied with 2 removable BIOCLIP stainless steel spouts L. 77mm. Independent IP65 electronic control unit. 230/12V mains supply with transformer. Base and spout with smooth interiors (reduces bacterial development). Adjustable duty flush (pre-set at ~60 seconds every 24 hours after last use). Flow rate limited to 4 lpm at 3 bar. Shock-resistant infrared presence detection sensor. Separate sensor for mounting on panels. M3/8" solenoid valve with integrated filter. Ø 60mm chrome-plated brass base. Anti-blocking security. Recommended installation height: 110 - 200mm above the basin surface. Electronic tap suitable for use in healthcare facilities, retirement and care homes, hospitals and clinics. Electronic tap suitable for people with reduced mobility. 30-year warranty. Two shut-off options: - standard mode: timed flow with automatic shut-off. - ON/OFF mode: user shuts off flow voluntarily or automatic shut-off after 30 minutes of flow.

Thermal shocks are possible.

Mount the sensor beside the tap in the ON/OFF mode.

TECHNICAL CHARACTERISTICS

TEMPOMATIC tap with BIOCLIP spout - Ref. 20804T2

Connector	3/8"
Technology	Wall-mounted electronic tap
Depth	190mm
Length	129mm
Spout length	188mm
Flow rate	4 lpm at 3 bar
Finish	Chrome-plated brass
Norms	ACS 🤆 🧐 🦉 🥥
Warranty	







Automatic duty flush limits bacterial development




Hygiene: spout can be removed and descaled inside



Hygiene: smooth interior reduces bacteria



No manual contact: infrared sensor



DELABIE

Repairability

