

# SECURITHERM shower panel

Ref. 79239015

Thermostatic mechanical dual control

2024 UK public price excluding VAT: £1,017.54

## DESCRIPTION

SECURITHERM shower panel - Ref. 79239015

Dual control thermostatic shower panel:  
 Anodised aluminium shower panel for wall-mounted, exposed installation.  
 Top inlet via in-line stopcocks and conical Ø 15mm inlets.  
 SECURITHERM thermostatic mixer.  
 Adjustable temperature control from cold water to 41°C.  
 Anti-scalding safety: automatic shut-off if cold or hot water supply fails.  
 Anti-cold showers function: automatic shut-off if hot water fails.  
 Thermal shocks are possible.  
 1/4 turn non-time flow valves.  
 Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.  
 Handset with removable flexible via rapid push-fit connector and wall-support supplied.  
 Concealed fixings.  
 Filters and non-return valves.  
 Suitable for people with reduced mobility.  
 30-year warranty.





## TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 79239015

Connector	M½" Ø 15mm
Technology	Non-time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS
Warranty	



## ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water supply fails
-  Fixed shower head or handset
-  Aluminium body, brass controls

