

SECURITHERM shower panel

Ref. 792410UK

Electronic battery-operated thermostatic

2024 UK public price excluding VAT: **£1,090.89**




DESCRIPTION

SECURITHERM shower panel - Ref. 792410UK





Electronic thermostatic shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 Concealed inlets via flexibles M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C: 1st limiter set at 38°C, 2nd limiter set at 41°C.
 Anti-scalding safety: immediate shut-off if cold or hot water supply fails.
 Thermal shocks are possible.
 Battery-operated with CR-P2 223 6V Lithium battery.
 Infrared presence detection. Shower starts when hand is 4cm from the sensor.
 Shuts off voluntarily or automatically after ~60 seconds.
 Duty flush (~60 seconds every 24 hours after the last use).
 Flow rate 6 lpm at 3 bar.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation.
 Concealed fixings.
 Filters and non-return valves.
 Electronic shower panel suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792410UK

Supply	6V battery
Connector	M1/2"
Technology	Electronic
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	thermostatic
Finish	Aluminium
Warranty	

ADVANTAGES

-  Total hygiene: operate without manual contact
-  Duty flush limits proliferation of bacteria
-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails

