

SECURITHERM shower panel

Ref. 792330

Thermostatic time flow dual control

2024 UK public price excluding VAT: £987.02




DESCRIPTION

SECURITHERM shower panel - Ref. 792330

SECURITHERM dual control thermostatic time flow shower panel:
 Anodised aluminium shower panel for wall-mounted, exposed installation.
 With concealed inlet via flexibles, M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Thermal shocks are possible.
 Soft-touch operation.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.
 2x ~30 second time flow valves to control fixed ROUND shower head and handset on flexible hose.
 Concealed fixings.
 Filters and non-return valves.
 Time flow shower panel suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792330

| | |
|---------------------|---|
| Connector | M $\frac{1}{2}$ " |
| Technology | Time flow |
| Height | 1050mm |
| Depth | 67mm |
| Width | 210mm |
| Flow rate | 6 lpm |
| Temperature limiter | Thermostatic |
| Finish | Aluminium |
| Norms | ACS   |
| Warranty |  |



ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  80% water savings
-  Aluminium body, brass controls

