

Auto-draining shower kit with EP mechanical mixer

Ref. 2539EPHYG

Shower kit with pressure-balancing mixer

2025 UK public price excluding VAT: £292.57

DESCRIPTION

Auto-draining shower kit with EP mechanical mixer - Ref. 2539EPHYG

Shower kit with single control mechanical mixer. SECURITHERM shower kit with auto-draining device:

- Mixer with Ø 40mm ceramic cartridge with pressure-balancing and pre-set maximum temperature limiter.






Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).
 Constant temperature regardless of pressure and flow rate variations.
 Flow rate regulated at 9 lpm.
 Chrome-plated brass body and sculptured control lever.
 M½" shower outlet with integrated non-return valve.
 Mixer with 2 offset STOP/CHECK wall connectors M1½" M3/4" ideal for hospitals.
 Filters and non-return valves.

- Chrome-plated shower head (ref. 813) with flexible hose (ref. 834T3) and chrome-plated, wall-mounted tilting support (ref. 845).
- Anti-stagnation connector FM½" for installation between lower outlet and flexible shower hose, for auto-draining of the flexible hose and shower head (ref. 880).

Shower kit ideal for healthcare facilities, nursing homes, hospitals and clinics. Suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

Auto-draining shower kit with EP mechanical mixer - Ref. 2539EPHYG

| | |
|---------------------|---|
| Connector | M1/2" |
| Technology | SECURITHERM EP |
| Width | 175mm |
| Flow rate | 9 lpm |
| Temperature limiter | 39°C |
| Finish | Chrome-plated brass |
| Norms |    |
| Warranty |  |
| Repairability |  |



ADVANTAGES

-  HW flow rate reduced if CW fails
-  Pressure-balancing: constant temperature
-  Ergonomic: sculptured lever is easy to grip
-  Water saving: flow rate regulated at 9 lpm

