

SECURITHERM EP pressure-balancing basin mixer

Ref. 2446LEPUK

Wall-mounted mixer, fixed spout L. 150mm, Hygiene lever L. 150mm

2024 UK public price excluding VAT: £388.95



DESCRIPTION

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446LEPUK

Wall-mounted SECURITHERM pressure balancing (EP) basin mixer. Wall-mounted mixer with flat, fixed under spout L. 150mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

Anti-scalding safety: HW flow rate is reduced if CW supply fails (and vice versa).

Stable temperature regardless of pressure and flow rate variations in the system.

Securitouch thermal insulation prevents burns.

Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.

Body and spout with smooth interior and low water volume (reduces bacterial development).

Flow rate regulated at 5 lpm.

Chrome-plated brass body.

Hygiene control lever L. 150mm..

Mixer supplied with in-line STOP/CHECK connectors M1/2" M3/4" ideal for use in hospitals.

Recommended installation height: 110 - 200mm above the basin surface.




Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2446LEPUK

Connector	M1/2"
Technology	SECURITHERM EP mixer, Securitouch
Spout length	150mm
Flow rate	5 lpm
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	
Warranty	
Repairability	

ADVANTAGES



EP: HW flow rate reduced if CW fails



Securitouch thermal insulation prevents burns



EP: limits pressure variations



Hygiene: smooth interior reduces bacteria

