

BINOPTIC electronic tap

Ref. 38801515

Mains supply, Ø 15mm compression fittings

2025 UK public price excluding VAT: £469.29



DESCRIPTION

BINOPTIC electronic tap - Ref. 38801515

Deck-mounted electronic basin tap:
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Chrome-plated brass body.
 PEX flexible with filter and solenoid valve Ø 15mm.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Spout with smooth interior and low volume of water (reduces bacterial development).
 Drop height: 170mm for semi-recessed washbasins.
 Suitable for people with reduced mobility.
 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 38801515

| | |
|--------------|---|
| Supply | Main supply 230/12 V |
| Connector | M1/2" Ø 15 |
| Technology | Electronic |
| Drop height | 170mm |
| Spout length | 175mm |
| Flow rate | 3 lpm |
| Norms |   |
| Warranty |  |

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

