## **BINOPTIC** electronic tap

Ref. 49801515

Battery-operated, Ø 15mm compression fittings

2024 UK public price excluding VAT: £590.05



## **DESCRIPTION**

BINOPTIC electronic tap - Ref. 49801515

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

Battery-operated with 123 6V Lithium batteries.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated brass body.

PEX flexible with filter and solenoid valve Ø 15mm.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Drop height: 250mm for countertop washbasins.

Suitable for people with reduced mobility.

30-year warranty.

## **ADVANTAGES**



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation




LED diagnostic aid

## TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 49801515

| Supply       | 6V batteries  |
|--------------|---------------|
| Connector    | M1/2" Ø 15    |
| Technology   | Electronic    |
| Drop height  | 250mm         |
| Spout length | 185mm         |
| Flow rate    | 3 lpm         |
| Norms        | WRAS          |
| Warranty     | 30 E WARRANTY |
|              |               |



© DELABIE https://www.delabie.co.uk