DELABIE

SECURITHERM shower panel

Ref. 792370

Thermostatic time flow

2024 UK public price excluding VAT: £1,026.78

DESCRIPTION

SECURITHERM shower panel - Ref. 792370

Thermostatic time flow shower panel: Anodised aluminium shower panel for wall-mounted, exposed installation. Top inlet via in-line stopcocks M¹/₂". SECURITHERM thermostatic mixer. Adjustable temperature control from cold water up to 38°C; with 1st limiter set at 38°C and 2nd limiter set at 41°C. Anti-scalding failsafe: automatic shut-off if the cold water fails. Anti-cold showers function: automatic shut-off if hot water fails. Thermal shocks are possible. Soft-touch operation. Handset with removable flexible via rapid push-fit STOP connector. ~30-second time flow valve for control of sliding handset on chrome-plated rail. Flow rate 6 lpm at 3 bar. Concealed fixings. Filters and non-return valves. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792370	
Connector	M ¹ / ₂ "
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	ACS
Warranty	30 g WARRANTY





Thermostatic temperature regulation



Immediate shut-off iff cold water fails







