

## TEMPOMIX 3 time flow mixer

Ref. 794350

Soft-touch operation

2025 UK public price excluding VAT: £369.82









### DESCRIPTION

TEMPOMIX 3 time flow mixer - Ref. 794350




Wall-mounted single control time flow basin mixer:  
 Soft-touch operation.  
 Temperature control and operation via the push-button.  
 Time flow pre-set at ~7 seconds.  
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
 Scale-resistant flow straightener.  
 Chrome-plated metal body M $\frac{1}{2}$ ".  
 Swivelling spout L. 150mm.  
 Filters and non-return valves.  
 Adjustable maximum temperature limiter.  
 M $\frac{1}{2}$ " offset connectors for centres from 130 - 170mm.  
 Suitable for people with reduced mobility.  
 30-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow mixer - Ref. 794350

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector    | M $\frac{1}{2}$ "                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Technology   | Time flow                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Length       | 200mm                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Width        | 150mm                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Spout length | 150mm                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Flow rate    | 3 lpm                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Norms        |      |
| Warranty     |                                                                                                                                                                                                                                                                                                                                                  |

### ADVANTAGES

-  Exceptional water savings: 85%
-  Soft-touch operation
-  Sleek and slim design

