SECURITHERM time flow shower kit

Ref. 792219

Thermostatic time flow, kit 2/2

2025 UK public price excluding VAT: £652.91





ADVANTAGES



Thermostatic temperature control



Instant shut-off if cold water fails



80% water savings

DESCRIPTION

SECURITHERM time flow shower kit - Ref. 792219

Recessed thermostatic time flow shower, kit 2/2:

Tamperproof polished satin stainless steel plate 195 x 220mm.

SECURITHERM thermostatic mixer ¾".

Anti-scalding failsafe: automatic shut-off if cold water fails.

Anti-cold showers function: automatic shut-off if hot water fails.

Adjustable temperature from 32° to 40°C, pre-set at 38°C.

Soft-touch operation.

Time flow ~30 seconds.

Flow rate set at 6 lpm at 3 bar.

Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.

Concealed fixings, M½" stopcocks.

Integrated non-return valves and filters.

Chrome-plated Bayblend® control knob.

Suitable for people with reduced mobility.

30-year warranty.

Order with waterproof housing ref. 792BOX.

TECHNICAL CHARACTERISTICS

SECURITHERM time flow shower kit - Ref. 792219

Connector	1/2"
Technology	Time flow
Height	195mm
Depth	110mm
Width	220mm
Flow rate	6 lpm
Finish	Satin finish stainless steel
Norms	ACS 🗓 🔘
Warranty	30 g

