

# TEMPOFLUX 3 AB side control flush system

Ref. 763300

Time flow valve AB, soft-touch side control, recessed

2025 UK public price excluding VAT: £447.89



## DESCRIPTION

TEMPOFLUX 3 AB side control flush system - Ref. 763300

Flush system without cistern: directly connected to pipework.  
Satin stainless steel access plate to mechanism 186 x 186mm.  
Satin stainless steel time flow control plate and chrome-plated buttons 90 x 90mm.

Control plate is installed manually via hidden screws.

Recessed waterproof housing:

- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment are integrated and accessible from the front.
- Cartridge and filter are accessible from the front.
- TEMPOFLUX 3 F $\frac{3}{4}$ " valve compatible with sea water, rain water and grey water.

- Backflow prevention device inside the housing.

Soft-touch operation.

AB anti-blocking system: water will flow only when the push-button is released.

3L/6L dual flush can be adjusted to 2L/4L.

Outlet connection for PVC tube  $\varnothing$ 26/32mm.

Acoustic level complies with European standard EN 12541 class II.

Upstream supply pipes: minimum  $\varnothing$  20mm required at all points (including connectors).

Base flow rate: 1 L/sec at 1 bar dynamic pressure.


Suitable for rimless WC pans without flow rate regulation.

Suitable for people with reduced mobility

30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 AB side control flush system - Ref. 763300

Connector	F $\frac{3}{4}$ "
Technology	Time flow side control
Length	186mm
Width	186mm
Finish	Satin stainless steel
Warranty	

## ADVANTAGES



Soft-touch side control, disabled-friendly



Satin stainless steel anti-blocking buttons/plates



Reliable system - Easy maintenance from front



3L/6L flush volume can be adjusted to 2L/4L

