

Recessing housing for thermostatic shower mixers

Ref. H96CBOX

Sequential mixer, kit 1/2

2024 UK public price excluding VAT: £331.29



DESCRIPTION


Recessing housing for thermostatic shower mixers - Ref. H96CBOX

Waterproof recessing housing for sequential thermostatic shower mixer, kit 1/2:

- Collar with waterproof seal.
 - Hydraulic connection from the outside and maintenance from the front.
 - Water supply connects from the top.
 - Adjusts to all types of installations (rails, solid walls, panels).
 - Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 83mm).
 - Suitable for standard or "pipe-in-pipe" supply.
 - Stopcocks and flow rate adjustment, filters and cartridge are all integrated and accessible from the front.
 - Sequential thermostatic shower mixer.
 - Supplied in 2 kits: secure system flush without sensitive elements.
- 30-year warranty.
Order with the control plate reference H9633.

TECHNICAL CHARACTERISTICS

Recessing housing for thermostatic shower mixers - Ref. H96CBOX

Connector	1/2"
Technology	SECURITHERM Securitouch sequential thermostatic mixer
Depth	80-110mm
Width	225mm
Norms	ACS
Warranty	

ADVANTAGES



Recessed installation



Modular and adjustable waterproof housing



Sequential mixer: no non-return valves



100% waterproof housing

