Recessed thermostatic sequential shower mixer

Ref. H9631

SECURITHERM mixer with no non-return valves, kit 2/2

2024 UK public price excluding VAT: £303.71



DESCRIPTION

Recessed thermostatic sequential shower mixer - Ref. H9631

SECURITHERM recessed thermostatic shower mixer, kit 2/2:

Thermostatic sequential shower mixer: opens/closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial development).

No risk of cross flow between the hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off immediately if cold water supply fails.

Prevents cold showers: shuts off immediately if hot water supply fails.

Sequential mixerc with Securitouch thermal insulation prevents burns.

Scale-resistant thermostatic sequential cartridge for adjusting flow rate and temperature.

Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head. ERGO controls.

M¾" inlets with integrated filters.

Order a wall-mounted outlet or shower head to complete.

Bright polished stainless steel cover plate 166 x 166mm.

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Sequential mixer ideal for people with reduced mobility.

Shower mixer with 30-year warranty.

Order with waterproof recessing housing ref. H96BOX.

ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety




Thermostatic: total temperature stability

TECHNICAL CHARACTERISTICS

Recessed thermostatic sequential shower mixer - Ref. H9631

Technology	SECURITHERM Securitouch thermostatic sequential shower mixer
Height	166mm
Width	166mm
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS WRAS
Warranty	30 g



DELABIE

Repairability



© DELABIE https://www.delabie.co.uk