

## Self-supporting fire retardant TEMPOFIX 3 frame system for WCs

Ref. 565065DE

For TEMPOFLUX 3

2024 UK public price excluding VAT: £783.15

### DESCRIPTION

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065DE

Self-supporting frame system for wall hung WCs, kit 1/2

Fire retardant CF 60 min - EI60.

Black powder-coated steel frame with large feet for load-bearing floors:

- Frame height can be adjusted from 0 - 200mm (with 1m mark).
- Ø 32mm flush tube with Ø 55mm connection washer and intumescent collar for fire protection.

- ABS soil pipe, Ø 110mm outlet to glue to waterproof seal, with 2 setting positions and intumescent collar for fire protection.

- Compatible with solid walls from 53 to 105mm (4 BA13 and tiles minimum).

Recessed waterproof housing with intumescent collar and fire protection set:

- Backflow prevention device inside the housing.

- Integrated stopcock and flow rate regulation.


Supplied pre-mounted.

30-year warranty.

Order with control plate reference 763000.

### TECHNICAL CHARACTERISTICS

Self-supporting fire retardant TEMPOFIX 3 frame system for WCs - Ref. 565065DE

|            |   |
|------------|---|
| Connector  | F $\frac{3}{4}$ "   |
| Technology | Time flow   |
| Height     | 1000 to 1320mm  |
| Depth      | 157 - 177mm   |
| Width      | 350mm   |
| Finish     | Black powder-coated steel   |
| Warranty   |  |



### ADVANTAGES



Fire retardant 60 minutes



Quick and easy to install: delivered pre-mounted



Space saving



Adapt to wall thickness

