BINOPTIC 2 electronic tap

Ref. 384130

Mains, recessed, L. 220mm

2024 UK public price excluding VAT: £491.11



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 384130

Recessed chrome-plated matte black electronic basin tap: 230/6V mains supply.

Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm. Scale-resistant aerator.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Wall-mounted stainless steel tap.

Presence detection sensor at the end of the spout optimises detection. Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

Set detection distance, duty flush and launch thermal shocks manually. Suitable for people with reduced mobility. 30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 384130

| Supply | 230/6V mains supply |
|--------------|---------------------------|
| Connector | M½" |
| Technology | Electronic |
| Spout length | 220mm |
| Flow rate | 3 lpm |
| Finish | Chrome-plated matte black |
| Norms | ACS |
| Warranty | 30g WARRANTY |

ADVANTAGES



Exceptional water savings: 90%




Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids



© DELABIE https://www.delabie.co.uk