BINOPTIC MIX 2 electronic basin mixer

Ref. 482110

Mains, cross wall 100mm, L. 220mm

2024 UK public price excluding VAT: £492.01



DESCRIPTION

BINOPTIC MIX 2 electronic basin mixer - Ref. 482110

Cross wall chrome-plated electronic basin mixer:

230/6V mains supply.

Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the mixer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.

Scale-resistant aerator.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Wall-mounted stainless steel mixer.

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces bacterial development).

 $\label{lem:side} \mbox{Side temperature control with adjustable maximum temperature limiter.}$

Set duty flush and launch thermal shocks manually.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush




Sleek design

TECHNICAL CHARACTERISTICS

BINOPTIC MIX 2 electronic basin mixer - Ref. 482110

| Supply | 230/6V mains supply |
|--------------|---------------------|
| Connector | F3/8" |
| Technology | Electronic |
| Spout length | 220mm |
| Flow rate | 3 lpm |
| Finish | Chrome-plated |
| Norms | ACS |
| Warranty | 30 WARRANTY |
| | |



© DELABIE https://www.delabie.co.uk