BINOPTIC 2 electronic tap

Ref. 374110E

Mains, deck-mounted, H. 170mm, Bluetooth®

2024 UK public price excluding VAT: £544.22



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 374110E

Deck-mounted satin electronic basin tap:

230/6V mains supply.

Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant aerator.

Adjustable duty flush (~60 seconds every 24 hours after the last use).

Stainless steel tap, 170mm high for semi-recessed basins.

Sensor at the end of the spout optimises detection.

PEX flexible with filter.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with smooth interior and low water volume (reduces niches where bacteria can develop).

Set presence detection range, duty flush and launch thermal shocks manually. Bluetooth* version: advanced settings and operating data download via DELABIE Connect app.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush




Easy to configure & monitor operation

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 374110E

Supply	230/6V mains supply
Connector	M3/8"
Technology	Electronic
Drop height	170mm
Flow rate	3 lpm
Finish	Chrome-plated
Norms	ACS
Warranty	30 g



© DELABIE https://www.delabie.co.uk