

SECURITHERM sequential thermostatic shower mixer

Ref. 9630

Thermostatique mixer with no non-return valves, bottom outlet

2024 UK public price excluding VAT: £359.12







DESCRIPTION

SECURITHERM sequential thermostatic shower mixer - Ref. 9630








SECURITHERM sequential thermostatic shower mixer.
 Sequential thermostatic mixer: opens and closes with cold water.
 Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
 No risk of cross flow between the hot and cold water.
 Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
 Prevents cold showers: shuts off automatically if hot water supply fails.
 Securitouch thermal insulation prevents burns.
 Scale-resistant sequential thermostatic cartridge adjusts the flow rate and the temperature.
 Temperature adjusts from cold water up to 39°C with temperature limiter set at 39°C.
 Thermal shocks are possible.
 Body with smooth interior and low water volume (reduces bacterial proliferation).
 Flow rate regulated at 9 l/min.
 Chrome-plated brass body and Hygiene lever L. 100mm.
 M1/2" bottom outlet.
 Mixer with no wall connectors with filters integrated in the inlets, F3/4".
 Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
 Sequential mixer suitable for people with reduced mobility.
 Shower mixer with 30-year warranty.

ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimum anti-scalding safety
-  Thermostatic: temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM sequential thermostatic shower mixer - Ref. 9630

Technology	SECURITHERM Securitouch sequential thermostatic shower mixer		
Length	184mm		
Flow rate	9 lpm at 3 bar		
Temperature limiter	YES		
Finish	Chrome-plated brass		
Norms	      		
Warranty	