

SECURITHERM sequential thermostatic shower mixer

Ref. 9630

Thermostatique mixer with no non-return valves, bottom outlet

2025 UK public price excluding VAT: £326.99







DESCRIPTION

SECURITHERM sequential thermostatic shower mixer - Ref. 9630








SECURITHERM sequential thermostatic shower mixer. Sequential thermostatic mixer: opens and closes with cold water. Mixer with no non-return valves on the inlets (reduces bacterial proliferation). No risk of cross flow between the hot and cold water. Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails. Prevents cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns. Scale-resistant sequential thermostatic cartridge adjusts the flow rate and the temperature. Temperature adjusts from cold water up to 39°C with temperature limiter set at 39°C. Thermal shocks are possible. Body with smooth interior and low water volume (reduces bacterial proliferation). Flow rate regulated at 9 l/min. Chrome-plated brass body and Hygiene lever L. 100mm. M1/2" bottom outlet. Mixer with no wall connectors with filters integrated in the inlets, F3/4". Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics. Sequential mixer suitable for people with reduced mobility. Shower mixer with 30-year warranty.

ADVANTAGES

-  Sequential: opens/closes with cold water
-  Maximum hygiene: no non-return valves
-  SECURITHERM: optimum anti-scalding safety
-  Thermostatic: temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM sequential thermostatic shower mixer - Ref. 9630

Technology	SECURITHERM Securitouch sequential thermostatic shower mixer
Length	184mm
Flow rate	9 lpm at 3 bar
Temperature limiter	YES
Finish	Chrome-plated brass
Norms	     
Warranty	
Repairability	